# SAFETY DATA SHEET

#### **LIGHTERS**

### Section 1. Identification

**GHS** product identifier

LIGHTERS

**Trade name** 

GRILLWORX HANDI LIGHTER, GRILLWORX E-Z SQUEEZE LIGHTER, GRILLWORX,

PUSH BUTTON LIGHTER 1PK, GRILLWORX PUSH BUTTON LIGHTER 2PK.

Product type : Liquefied gas lighter

Identified uses : Multi-Purpose Utility Lighters

Supplier/Manufacturer : Mayo Hardware Pty Ltd

4 Secombe Place,

Moorebank, NSW, 2170

1300 360 211

**Emergency telephone** 

number

CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER

N.A. Toll Free: 1-800-255-3924 International: 01-813-248-0585

### Section 2. Hazards identification

OSHA/HCS status : HAZARDOUS CHEMICAL according to the criteria of Safe Work Australia.

DANGEROUS GOODS according to the criteria of the ADG Code.

Classification of the substance or mixture GHS label elements : FLAMMABLE GASES – Category 1

GASES UNDER PRESSURE – Liquefied gas

Hazard pictograms :





Signal word : Danger

**Hazard statements**: Extremely flammable gas.

Contains gas under pressure; may explode if heated.

**Precautionary statements** 

Response

Prevention : P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Vapors may travel to source of ignition and flash back. May vent and release flammable gas through pressure relief devices. Do not inhale contents. P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

Storage P410 + P403 Protect from sunlight. Store in well-ventilated place. Do not

expose to temperatures exceeding 50°C.

Other hazards Vapours may travel to source of ignition and flash back. May vent and release

flammable gas through pressure relief devices.

Mayo Hardware Pty Ltd 1/10

Mayo Hardware Pty Ltd Page 1/8

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Name	%	CAS number
Butane	80 – 100	106-97-8
Propane	0 – 20	74-98-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment. Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Inhalation

Skin contact

**Swallowing** 

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if safe and easy to do.

Continue to rinse for at least 20 minutes. Get medical attention if irritation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Flush contaminated skin with plenty of water. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. In case of contact with liquid, warm frozen skin slowly with lukewarm water and get medical attention. Do not rub affected area. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if adverse health effects persist or are severe. Ingestion of liquid can cause bloating as the gas expands, and burns similar to frostbite. If ingestion occurs, get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. As this product rapidly becomes a gas when released, refer to the inhalation section.

#### Most important symptoms/effects, acute and delayed

#### **Potential acute health effects**

Eye contactInhalationLiquid can cause burns similar to frostbite.No known significant effects or critical hazards.

Skin contact : Dermal contact with rapidly evaporating liquid could result in freezing of the

tissues or frostbite.

**Ingestion**: Ingestion of liquid can cause burns similar to frostbite.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following: frostbite

Inhalation : No known significant effects or critical hazards.

Skin contact: Adverse symptoms may include the following: frostbiteIngestion: Adverse symptoms may include the following: frostbite

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

**Extinguishing media** 

**Suitable extinguishing** 

media

**Unsuitable extinguishing** 

None known.

media

Specific hazards arising from the chemical

Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion.

SMALL FIRE: Use dry chemical or CO<sub>2</sub>. LARGE FIRE: Use or water spray or fog.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
 Carbon dioxide

Carbon monoxide

Special protective actions for fire-fighters

Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shot off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to urn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.

Special protection equipment for firefighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. For incidents involving large quantities, thermally insulated undergarments and thick textile or leather gloves should be worn.

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specializes clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

**Small spill** 

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion proof equipment.

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Use sparkproof tools and explosion proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

Protective measures :

Contains gas under pressure. Store in cool, ventilated area. Store away from heat, sparks, open flame, direct sunlight and temperatures exceeding 50°C, Do not puncture or inciperate container.

puncture or incinerate container.

Advice on general

handling

No smoking.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep

container tightly closed and sealed until ready for use.

1900 mg/m<sup>3</sup>

# Section 8. Exposure controls/personal protection

#### Australia

**Exposure Standards** Safe Work Australia

Propane 74-98-6 Asphyxiant
Butane 106-97-8 TWA: 800ppm

**Appropriate engineering** 

controls

Use only with adequate ventilation. No specific ventilation required for normal use. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas concentrations below any lower explosive limits. Use explosion-proof ventilation

equipment.

#### **Individual protection measures**

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working period. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Not required under normal conditions of use.

Hand protectionBody protectionNot required under normal conditions of use.Not required under normal conditions of use.

Other skin protection

: Not required under normal conditions of use.

**Respiratory protection**: Use suitable respiratory protective device in case of insufficient ventilation.

### Section 9. Physical and chemical properties

**Appearance** 

Physical State : Gas. [Liquefied gas]

Colour : Colourless.

Odor : Odorless or can have a faint gas odour.

Odor threshold : Not available.

PH : Not available.

Melting point : Not available.

Boiling point : -15 to 0°C

Flash point : Closed cup: -90 to -73°C

**Evaporation rate** : Not available.

Mayo Hardware Pty Ltd

Flammability (solid, gas) : Flammable in the presence of the ignition sources: open flames, sparks and

static discharge and heat.

# Section 9. Physical and chemical properties

Lower and upper : Lower: 1.8% explosive (flammable) Upper: 8.8%

limits

Vapor pressure : 150 to 250 kPa [room temperature]

Vapor density : 2 [Air = 1] Relative density : 0.56 g/cm<sup>3</sup>

**Solubility**: Insoluble in the following materials: cold water and hot water.

Partition coefficient : n-

octanol/water

Not available.

**Auto-ignition** : Not available.

temperature

**Decomposition**: Not available.

temperature

Viscosity : Not available.

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its

ingredients.

**Chemical stability**: This product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not smoke.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials and

acids.

**Hazardous**: Under normal conditions of storage and use, hazardous decomposition products

**decomposition products** should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

**Acute toxicity** 

There is no data available.

**Irritation/Corrosion** 

There is no data available.

Sensitization

There is no data available.

Carcinogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

**Aspiration hazard** 

There is no data available.

**Information on the likely** : Not available.

routes of exposure

Mayo Hardware Pty Ltd Page 5/8

Potential acute health effects

Eye contactInhalationLiquid can cause burns similar to frostbite.No known significant effects or critical hazards.

Skin contact : Dermal contact with rapidly evaporating liquid could result in freezing of the

tissues or frostbite.

**Ingestion**: Ingestion of liquid can cause burns similar to frostbite.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

Frostbite

Inhalation : No known significant effects or critical hazards.Skin contact : Adverse symptoms may include the following:

**Frostbite** 

**Ingestion** : Adverse symptoms may include the following:

Frostbite

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential and immediate**: No known significant effects or critical hazards.

effects

**Potential delayed effects**: No known significant effects or critical hazards.

Long term exposure

**Potential and immediate** : No known significant effects or critical hazards.

effects

**Potential delayed effects**: No known significant effects or critical hazards.

**Potential chronic health effects** 

**General**: No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

**Acute toxicity estimates** No data available

# Section 12. Ecological information

Toxicity : There is no data available Persistence and : There is no data available

degradability

Bioaccumulative : There is no data available

potential Mobility in soil

## Section 12. Ecological information

Soil/water partition : Not available.

coefficient (K<sub>OC</sub>)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : Disposal must be made in compliance with the requirements of local and

federal hazmat and waste disposal regulations.

Do not pierce or dispose of in a fire, even when empty.

Mayo Hardware Pty Ltd Page 7/8

## Section 14. Transport information

	ADG Code	IMDG	IATA
UN number	UN1057	UN1057	UN1057
UN proper shipping name	Lighters	Lighters	Lighters
Transport	2.1	2.1	2.1
hazard class(es)	PLAMMABLE GAS	PLAMIABLE GAS	FLAMMABLE GAS
Packing group	None	None	None
Environmental hazards	No	No	No

**AERG** : 115

**Special precautions for** 

user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know

what to do in the event of an accident or spillage.

## Section 15. Regulatory information

**Australia** 

AIIC All ingredients listed SUSMP Not scheduled

ACCC Mandatory Product Safety Standard applies

### Section 16. Other information

**History** 

**Date of issue** : 07/06/2021

Version : 1

Revised Section(s) : Not applicable.

Prepared by : Tokai of Canada, LTD. Website: <a href="https://www.tokai.ca">www.tokai.ca</a>

Adapted for Australia by RG Chemical Safety

**Key to abbreviations** : ATE = Acute Toxicity Estimate

ADG Code = Australian Dangerous Goods Code

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

Log Pow = logarithm of the octanol/water partition coefficient

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Mayo Hardware Pty Ltd Page 8/8